

300x600 Stamford Matt Floor Tiles

PORCELAIN TILES ARE PRODUCED CONFORMING TO SPECIFICATION OF MS ISO 13006 : 2014, GROUP Bla E ≤ 0.5%

TEST DESCRIPTION	INDUSTRY STANDARD	REQUIREMENT	TEST RESULT
Nominal Size		30 x 60cm	30 x 60cm
Work Size		299.5 x 600.0 x 8.5mm	299.5 x 600.0 x 8.5mm
Dimension and Surface Quality			
Length & Width	ISO 10545-2	± 0.6 %	± 0.2 %
Thickness	ISO 10545-2	± 5.0 %	± 5.0 %
Edge Straightness	ISO 10545-2	± 0.5 %	± 0.3 %
Rectangularity	ISO 10545-2	± 0.6 %	± 0.3 %
Planarity (Flatness)	ISO 10545-2	± 0.5 %	± 0.3 %
Surface quality	ISO 10545-2	Minimum 95 %	Conforms
Physical Properties			
Water Absorption	ISO 10545-3	E ≤ 0.5%	E ≤ 0.5%
Modulus of Rupture	ISO 10545-4	≥ 35 N/mm ²	≥ 35 N/mm ³
Breaking Strength, in N	ISO 10545-4	≥ 1300 N	≥ 1300 N
Crazing Test	ISO 10545-11	Required	No Visible Defects
Abrasion Resistance	ISO 10545-7	Report Abrasion class and cycles passed	Min Class 3
Chemical Properties			
Chemical resistance to:			
a) Concentrated Acids and Alkalis	ISO 10545-13	GA	GLA
Staining Resistance	ISO 10545-14	No Permanent Staining	Min Class 3
Slip Resistance - Wet Pendulum (Factory Test)	AS 4586 / BS7976	Declare Value	P3

The above Johnson Tiles technical specifications are a general indication only.

Please contact your local Johnson Tiles representative or state office for more detailed information.