

Nordik Floor Tiles

Dimensions and Surface Quality	Specifications (Matt)
Nominal size (mm)	300x600x9mm
Working size (mm)	296x596x9mm
Dimensions (mm)	296.0 ± 0.3 596.0 ± 0.4
Thickness (mm)	8.8 ± 0.5
Straightness of Sides (mm)	-0.3 ~ + 0.3
Measurement of diagonal (mm)	≤ 0.8
Measurement of wedging (mm)	≤ 0.6
Centre Curvature (mm)	-0.5 ~ + 1.0
Edge Curvature (mm)	-0.5 ~ + 1.0
Warpage (mm)	-0.5 ~ + 1.0
Surface Quality (%)	≥ 95% no defect noticeable from the sight of 0.8m
Water Absorption (%)	E ≤ 0.5
Modulus of Rupture (Mpa)	≥ 35
Breaking Strength (N)	Average ≥ 1300
Abrasion Resistance	Class 3
Crazing Resistance	No cracks found with 5 cycle test
Resistance to Chemicals: HCL KOH	≥ GLB ≥ GLB
Resistance to Staining: Blue ink Potassium permanganate	≥ Class 3 ≥ Class 3
Slip Resistance	P3

The above Johnson Tiles technical specifications are a general indication only. Please contact your local Johnson Tiles representative or state office for more detailed information.