

# Technical Data Sheet

## Rustic

### Rustic Floor Tiles

<b>Test Description</b>			
Wet Pendulum	P2		
Oil Wet Ramp			
<b>Specifications</b>			
Nominal Size	300x300x8.4		
Work Size	300x300x8.2		
<b>Dimensions and Surface Quality</b>	<b>Specifications</b>		
Thickness	8.2±0.2mm		
Straightness of Sides	+0.7mm		
Rectangularity	+0.7mm		
a) Centre Curvature	-0.4+1mm		
b) Edge Curvature	-0.4+0.7mm		
c) Warpage	-0.4+0.7mm		
Surface Quality	≥95% no defect noticeable from the sight of 0.8m		
<b>Physical Properties</b>			
Water Absorption	≤6.0		
Breaking Strength (N)	≥1100N		
Modulus of Rupture	≥32		
Crazing Test	No Craze		
Abrasion Resistance	Light Brick Level 4 Dark Brick Level 3		
<b>Chemical Properties</b>			
a) Household chemicals	≥GLB		
b) Swimming Pool Salt	≥GLB		
c) Acid and Alkalis	≥GLB		
	Blue Ink	≥Grade 3	



Staining Resistance	Potassium Permanganate	≥Grade 3		
Coefficient of friction	(Dry)	≥0.6		
	(Wet)	≥0.4 - ≥0.5		
MS ISO 13006: 2003, GROUP				
MS ISO 13006: 2003, GROUP				

The above Johnson Tiles technical specifications are a general indication only. Please contact your local Johnson Tiles representative or state office for more detailed information.

